

#### 8.9.4 Proper selection of PUR – MEP and Ewelcon open (plate type) electro-fusion welding joints

Standard insulation foaming length Lw=440mm			
JACKET PIPE external diameter Dz: [mm]	STEEL PIPE nominal diameter DN: [mm]	Foam-bags or foam-kits (bottled)	CATALOGUE No.
90	20	0,5	PURSw-090/20L440 PURS-090...
90	25	0	PURSw-090/25L440 PURS-090...
110	32	0,5	PURSw-110/32L440 PURS-110...
110	40	0,5	PURSw-110/40L440 PURS-110...
125	50	1	PURSw-125/50L440 PURS-125...
140	65	2	PURSw-140/65L440 PURS-140...
160	80	3	PURSw-160/80L440 PURS-160...
180	80	4	PURSw-180/80L440 PURS-180...
200	100	5	PURSw-200/100L440 PURS-200...
225	125	6	PURSw-225/125L440 PURS-225...
250	150	6	PURSw-250/150L440 PURS-250...
280	150	8	PURSw-280/150L440 PURS-280...
315	200	8	PURSw-315/200L440 PURS-315...
355	200	10	PURSw-355/200L440 PURS-355...
400	250	2x7	PURSw-400/250L440 PURS-400...
450	300	11	PURSw-450/300L440 PURS-450...
500	350	7+10	PURSw-500/350L440 PURS-500...
520	400	5+10	PURSw-520/400L440 PURS-520...
560	450	5+10	PURSw-560/450L440 PURS-560...
630	500	13	PURSw-630/350L440 PURS-630...
800	600	11+14	PURSw-800/600L440 PURS-800...
800	700	13	PURSw-800/700L440 PURS-800...
900	700	13+14	PURSw-900/500L440 PURS-900...
1000	800	2x14	PURSw-1000/800L440 PURS-1000...
1100	900	2x15	PURSw-1100/900L440 PURS-1100...

**\*Other diameters available on request**