

8.9.3 Proper selection of PUR – flexible elbow joints with shrinkable ends (Flexbends)

Insulation standard, PLUS and PLUS+, overlap on the jacket pipe L:120mm				
JACKET PIPE external diameter Dz: [mm]	STEEL PIPE nominal diameter DN: [mm]	Foam-bags or foam-kits (bottled)	Foaming length L _w : [mm]	CATALOGUE No.
90	20/26,9	4	740	PURFw-090/20L740 PURF-090...
90	25/33,7	4	740	PURFw-090/25L740 PURF-090...
110	20/26,9	5	740	PURFw-110/20L740 PURF-110...
110	25/33,7	5	740	PURFw-110/25L740 PURF-110...
110	32/42,4	5	740	PURFw-110/32L740 PURF-110...
110	40/48,3	5	740	PURFw-110/40L740 PURF-110...
125	20/26,9	7	810	PURFw-125/20L810 PURF-125...
125	25/33,7	2x3	810	PURFw-125/25L810 PURF-125...
125	32/42,4	2x3	810	PURFw-125/32L810 PURF-125...
125	40/48,3	2x3	810	PURFw-125/40L810 PURF-125...
125	50/60,3	6	810	PURFw-125/50L810 PURF-125...
140	32/42,4	2x4	810	PURFw-140/32L810 PURF-140...
140	40/48,3	2x4	810	PURFw-140/40L810 PURF-140...
140	50/60,3	7	810	PURFw-140/50L810 PURF-140...
140	65/76,1	7	810	PURFw-140/65L810 PURF-140...
160	32/42,4	3+7	810	PURFw-160/32L810 PURF-160...
160	40/48,3	3+7	810	PURFw-160/40L810 PURF-160...
160	50/60,3	9	810	PURFw-160/50L810 PURF-160...
160	65/76,1	9	810	PURFw-160/65L810 PURF-160...
160	80/88,9	8	810	PURFw-160/80L810 PURF-160...
180	50/60,3	4+8	810	PURFw-180/50L810 PURF-180...
180	65/76,1	2x6	810	PURFw-180/65L810 PURF-180...
180	80/88,9	4+7	810	PURFw-180/80L810 PURF-180...
200	65/76,1	2x8	880	PURFw-200/65L880 PURF-200...
200	80/88,9	11	880	PURFw-200/80L880 PURF-200...
200	100/114,3	5+9	880	PURFw-200/100L880 PURF-200...
225	80/88,9	13	980	PURFw-225/80L980 PURF-225...
225	100/114,3	5+11	980	PURFw-225/100L980 PURF-225...
225	125/139,7	6+10	980	PURFw-225/125L980 PURF-225...
250	100/114,3	14	1100	PURFw-250/100L1100 PURF-250...
250	125/139,7	7+12	1100	PURFw-250/125L1100 PURF-250...
250	150/168,3	9+10	1100	PURFw-250/150L1100 PURF-250...

* foam-bags doses for diameters 280, 315, 355, 400 in pipeline