

9.14 DM copper wire and DMC tin-coated copper wire, diameter 1,39mm.



ITEM	CATALOGUE No.
DM copper wire	DAM-139
DMC copper tin-coated wire	DAMC-139

Wire diameter 1.39mm (cross-section 1.5mm²) for alarm systems of pre-insulated pipes, in rolls of ca. 20kg each (1kg=74 meters of wire).

9.15 PDA bracket (support) for alarm wire.



PRODUCT NAME	Height [mm]	CATALOGUE No.
Support	15	PDA-15
Support	36	PDA-36

Supports are used for assembly of insulating of the joints at building-site, to support alarm wires in proper position during PUR foaming.

Supports are available in two different height versions.

9.16 Brandes set.



ITEM	CATALOGUE No.
Non-pass-through connector Brandes	ZDBN
Heat-shrinkable sleeve Brandes	TTDB

9.17 ZDA connector for 1,39mm alarm wire.



PRODUCT NAME	CATALOGUE No.
Non-pass-through, tin-coated connector	ZDAN-139
tin-coated pass-through connector	ZDAP-139

9.18 Tape for fixing the PDA brackets.



ITEM	CATALOGUE No.
Fixing tape to PDA brackets	TDP

Paper tape for fixing the PDA brackets, temperature resistant.

9.19 An alarm wire outlet.



ITEM	Diameter D [mm]	CATALOGUE No.
Alarm wire outlet	32/16/18	WDA 3216
	32/20/20	WDA 3220
	32/22/20	WDA 3222
	32/25/20	WDA 3225

The alarm wire outlet is made of HDPE100 material.